



**ANSWER:** Mud flaps are permissible provided that they are splash and spray suppressant type.

**7. QUESTION: Section G (Detachable Neck), Specification 8...** Air activated, self-locking pin on gooseneck for positive lock. (Manual lock not acceptable) We offer a hydraulic activated self-locking system to ensure a positive lock. Is this acceptable?

**ANSWER:** No, air activated lock required.

**8. QUESTION: Section I (Suspension, Tires and Wheels), Specification 1...** Tires are to be 255/70R22.5. 16 Ply LR H. We offer 275/70R22.5 16 Ply LR H. Is this acceptable?

**ANSWER:** No, this is a tire standard within our fleet.

**9. QUESTION: Section I (Suspension, Tires and Wheels), Specification 6...** Axle spacing to be 55" We offer our axle spacing to be 54". Is this acceptable?

**ANSWER:** Axle spacing range of 54" to 56" will be acceptable.

**BID OPEN DATE REMAINS AS SCHEDULED ON JANUARY 20, 2015 @ 3:00 PM E.S.T.**

---

Offerors must acknowledge receipt of this amendment by one of the following methods: (a) By signing and returning one copy of this amendment with your bid; (b) By acknowledging receipt of this amendment on each copy of the bid submitted; or separate letter which includes a reference to the solicitation and amendment numbers. Failure of your acknowledgment to be received at the Purchasing Office prior to the hour and date of the opening may result in rejection of your offer. If by virtue of this amendment you desire to change an offer already submitted, such change may be made by letter, provided such letter makes reference to the solicitation and this amendment and is received prior to the opening hour and date specified.

---

Kay Keisler  
Procurement Officer

CONTRACTOR: \_\_\_\_\_

NAME & TITLE OF AUTHORIZED REPRESENTATIVE \_\_\_\_\_

AUTHORIZED SIGNATURE \_\_\_\_\_

---

Jeffrey A. Hyde, CPPB  
Procurement Manager